

Product datasheet

Specifications



Device monitoring and management, Network Management Cards, NMC3, secure remote UPS monitoring and management

AP9640

Overview

Lead time Usually in Stock

Main

Range of product Network Management Cards

Range compatibility
Galaxy VM
Galaxy VX
Symmetra PX
Easy UPS 3M Advanced
Easy UPS 3-Phase Modular
Galaxy PX
Galaxy 3L Pro
Smart-UPS
Smart-UPS Ultra
Smart-UPS Online
Smart-UPS Modular Ultra
Smart-UPS Battery Systems
Back-UPS SX3
Refurbished Smart-UPS

Product or component type Device monitoring and management

Provided equipment
Micro-USB cable
Installation manual

Number of input phases
1
3

Standards
EN 55024
BS EN 55024
EN 61000-4-2
BS EN 61000-4-2
EN 61000-4-3
BS EN 61000-4-3
EN 61000-4-4
BS EN 61000-4-4
EN 61000-4-5
BS EN 61000-4-5
EN 61000-4-6
BS EN 61000-4-6
EN 61000-4-8
BS EN 61000-4-8
EN 61000-4-11
BS EN 61000-4-11
EN 55035
BS EN 55035
EN 62040-2
BS EN 62040-2
EN 61326-2
BS EN 61326-2
ICES-003 class A
VCCI class A
EN 61000-6-3
BS EN 61000-6-3
EN 55032: class A
BS EN 55032: class A

Physical

Net weight	0.08 kg
Width	12.1 cm
Height	3.8 cm
Depth	11.4 cm

Conformance

Product certifications	FCC Class A AS/NZS AS/NZS 3548 (C-Tick) class A FCC part 15 class A GOST UK PSTI
-------------------------------	---

Environmental

Storage Relative Humidity	0...95 %
Relative humidity	0...95 %
Ambient air temperature for storage	-15...65 °C
Ambient air temperature for operation	-5...45 °C
Storage altitude	0...15240 m
Operating altitude	0...10000 ft

Communications & Management

Communication network type	10/100/1000BASE-T
Authentication	Radius Lightweight Directory Access Protocol (LDAP)
Communication port protocol	HTTP over secure sockets Layer (HTTPS) SSH FTP HTTP SNMP DHCP BOOTP (Bootstrap Protocol) TCP/IP

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	5.1 cm
Package 1 Width	15.9 cm
Package 1 Length	23.5 cm
Package 1 Weight	0.34 kg

Contractual warranty

Warranty (in months)	24
-----------------------------	----



Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

[Environmental Data explained >](#)

[How we assess product sustainability >](#)

Environmental footprint

Total lifecycle Carbon footprint 110

Environmental Disclosure [Product Environmental Profile](#)

Use Better

Materials and Substances

Packaging made with recycled cardboard No

Packaging without single use plastic No

[EU RoHS Directive](#) Compliant

SCIP Number 1cdb2fed-a06f-4574-913d-8df8e70936b2

REACH Regulation [REACH Declaration](#)

Use Longer

Lifetime extension

Repair No

Use Again

Repack and remanufacture

End of life manual availability [End of Life Information](#)

Removable battery Yes

Take-back No

WEEE Label The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins

Image of product / Alternate images

Alternative

