

Product datasheet

Specifications



APC NetShelter Basic Rack PDU, 1U, 1 phase, 3.7kW 230V 16A or 3.3kW 208V 16A, 12 C13 outlets, C20 cord

AP9565

Overview

Presentation Reliable rack power distribution designed to increase manageability and efficiency in the data center The output and input connections are (12)C13 Real-time remote monitoring of connected loads User-defined alarms warn IT and data center managers of potential circuit overloads to prevent accidental power loss to critical equipment.

Lead time Usually in Stock

Main

Colour Black

Product or component type PDU

PDU type Basic

Cord length 2.49 m

Number of cables 1

Provided equipment Installation guide
Rack mounting brackets

Complementary

Input Voltage 200 V
208 V
230 V

Height 44 mm

Width 447 mm

Output Voltage 208 V
230 V

Depth 57 mm

Net weight 2.05 kg

Mounting location Front
Rear

Mounting preference No preference

Input Plug Type IEC 60320 C20

Mounting mode Rack-mounted

Rack units 1U

Mounting position Horizontal

Input current limits 16 A

Load capacity 3680 VA

Network frequency 50/60 Hz

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

Outlet type and quantity	12 IEC 60320 C13
--------------------------	------------------

Environment

Product certifications	cUL listed CE Queensland Australia UL listed VDE
------------------------	--

Standards	UL 60950
-----------	----------

Ambient air temperature for operation	0...45 °C
---------------------------------------	-----------

Relative humidity	0...95 %
-------------------	----------

Operating altitude	0...10000 ft
--------------------	--------------

Ambient air temperature for storage	-25...65 °C
-------------------------------------	-------------

Storage Relative Humidity	0...95 %
---------------------------	----------

Storage altitude	0...15240 m
------------------	-------------

Packing Units

Unit Type of Package 1	PCE
------------------------	-----

Number of Units in Package 1	1
------------------------------	---

Package 1 Height	7 cm
------------------	------

Package 1 Width	46.4 cm
-----------------	---------

Package 1 Length	22.9 cm
------------------	---------

Package 1 Weight	3.632 kg
------------------	----------

Contractual warranty

Warranty (in months)	24
----------------------	----



Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

[Environmental Data explained >](#)

[How we assess product sustainability >](#)

Environmental footprint

Total lifecycle Carbon footprint 2398

Environmental Disclosure [Product Environmental Profile](#)

Use Better

Materials and Substances

Packaging made with recycled cardboard Yes

Packaging without single use plastic No

[EU RoHS Directive](#) Compliant

SCIP Number 1cdb2fed-a06f-4574-913d-8df8e70936b2

REACH Regulation [REACH Declaration](#)

Halogen-free status Product contains halogen above thresholds

Use Longer

Lifetime extension

Repair No

Use Again

Repack and remanufacture

End of life manual availability [End of Life Information](#)

Take-back No

WEEE Label The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins

Image of product / Alternate images

Alternative



